

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A battery pack comprising: a plurality of parallel arranged battery modules (2), each battery module (2) consisting of a plurality of cells (5) formed by encasing elements for electromotive force in prismatic cases, the cells (5) being electrically connected in series and coupled together in one piece with gaps (8) formed therebetween; and a restraining tool having connecting members (4) extending through the gaps at both ends of the parallel arranged battery modules and between two given cells.

2. (Currently Amended) The battery pack according to claim 1, wherein a connection terminal (6, 7) for electrically connecting the cells (5) with each other is protruded on one of opposing side faces of the cells such as to form gaps (8) between the opposing side faces of the cells that make up the battery module (2).

3. (Currently Amended) The battery pack according to claim 1,
wherein the restraining tool comprises end plates (3) arranged at both ends
in an alignment direction of the battery modules (2), and both ends of the
connecting members (4) are coupled to the end plates.

4. (Currently Amended) The battery pack according to claim 1,
wherein components for forming cooling medium passages (16) between
side faces of the cells (5) are provided between the parallel arranged
battery modules (2).

5. (Currently Amended) The battery pack according to claim 4,
wherein the components forming the cooling medium passages (16) are
formed of separate spacer portions (12) independently of the battery
modules (2).

6. (Currently Amended) The battery pack according to claim 4,
wherein the cell (5) cases are made of a metal and the components
forming the cooling medium passages (16) are insulating spacer portions
(12) provided independently of the battery modules (2).

7. (Currently Amended) The battery pack according to claim 5,
wherein the spacer portions (12) have holder portions (13) that fit in the
gaps (8) between the cells (5, 5) for positioning the cells.

8. (Currently Amended) The battery pack according to claim 5,
wherein the spacer portions (12) have projections (15) that abut on the long
side faces of the cells (5) to form the cooling medium passages (16).

9. (Currently Amended) The battery pack according to claim 8,
wherein heat dissipation fins (17, 30) facing the cooling medium passages
(16) are provided on the long side faces of the cells (5).

10. (Currently Amended) A battery pack comprising: a plurality of parallel arranged battery modules (2), each battery module (2) consisting of a plurality of cells (5) formed by encasing elements for electromotive force in prismatic cases, the cells (5) being electrically connected with each other in series by connection terminals (6, 7) protruded on side faces thereof; holders (11) for the battery modules disposed between parallel arranged adjacent battery modules; end plates (3) arranged at both ends in an alignment direction of the battery modules; and connecting members (4) extending through gaps (8) at both ends of the battery modules and between two given cells and coupling both end plates together, wherein each holder includes a spacer portion (12) forming a cooling medium passage (16) between side faces of the cells and holder portions (13) provided on both sides of the spacer portion at locations corresponding to both sides of each cell for engaging with and retaining the cells.

11. (Currently Amended) The battery pack according to claim 10, wherein the connection terminals ~~(6, 7)~~ of the cells ~~(5)~~ are protruded on short side faces of the cell cases, and the cooling medium passages ~~(16)~~ are formed between the long side faces of the cells.

12. (Currently Amended) The battery pack according to claim 10, wherein the holder portions ~~(13)~~ of the holders ~~(11)~~ engage with generally half or less of the width of the short side faces of the cells ~~(5)~~.

13. (Currently Amended) The battery pack according to claim 10, wherein the cell ~~(5)~~ cases are made of a metal and the holders ~~(11)~~ are made of an insulating material.

14. (Currently Amended) The battery pack according to claim 10, wherein the holder ~~(11)~~ includes support portions ~~(20)~~ at both ends, which are placed on support members, and one of the support portions is provided with a fixing bolt hole or screw hole ~~(22)~~.

15. (Currently Amended) The battery pack according to claim 14, wherein the support portions ~~(20)~~ at both ends of the holders ~~(11)~~ are formed with an engaging protrusion ~~(23)~~ on one side and an engaging recess ~~(24)~~ on the other side in which the engaging protrusion fits.

16. (Currently Amended) The battery pack according to claim 10,
wherein the holder portions (13) of the holders (11) include support
projections (31) on the top and the bottom, which are engaged with an
upper case (34) and a lower case (33) covering the battery pack.

17. (Currently Amended) The battery pack according to claim 10,
wherein the spacer portions (12) have projections (15) that abut on the long
side faces of the cells (5) to form the cooling medium passages (16).

18. (Currently Amended) The battery pack according to claim 17,
wherein heat dissipation fins (17, 30) facing the cooling medium passages
(16) are provided on the long side faces of the cells (5).

19. (Currently Amended) The battery pack according to claim 1,
wherein the connecting members (4) are arranged on both sides of each of
the cells (5) of the battery modules (2).

20. (Currently Amended) The battery pack according to claim 4,
wherein heat dissipation fins (17, 30) forming the cooling medium
passages (16) are provided on the long side faces of the cells (5).

21. (Currently Amended) The battery pack according to claim 9,
wherein the heat dissipation fins (17, 30) are resiliently pressed against the
long side faces of the cells (5) by pressure applied from the spacer portions
(12) forming the cooling medium passages (16).